



Key Features

- Five part numbers to cover 41 channels in the C-band with 100GHz grid spacing
- Up to 40km link length single mode fiber point-to-point and multi-point passive networks
- Supports data rates between 1Gbps and 11.3Gbps
- Operating temperature range -40°C to +85°C
- SFP+ Multi-Source Agreement compliant (SFF-8083, rev. 1.7)
- SFF Tunability Interface (SFF-8690, rev. 1.4)
- Support for digital diagnostics and monitoring (SFF-8472, rev. 12.2)
- Dual LC connector, hot pluggable with SFP+ footprint
- Limiting receiver electrical interface
- Power dissipation <2.0W over operating temperature range
- Optional NarroWave support enables Wavelength Auto-Tuning and Remote Diagnostics

Overview

EFFECT Photonics' 10Gbps Narrow Tunable SFP+ optical transceiver module is designed to operate at transmission rates from 1Gbps to 11.3Gbps, compatible with multiple network applications and transmission formats: CPRI, OTN, Fibre Channel, etc. Hot pluggable, and with narrow band tunability, it significantly reduces sparing and configuring costs in optical networks. The module is optimized for Local Area Networks (LAN), Mobile Fronthaul and 10G Ethernet (10GbE), over single-mode fiber (SMF) optical links, P2P and passive networks.

On the transmit side, the serial data path from the host enters the module through the electrical connector and enters the modulator driver. The modulator driver accurately biases and efficiently modulates EFFECT Photonics' Optical System-on-Chip which contains the tunable 1550nm cooled laser and Mach-Zehnder Interferometer (MZI) modulator and transmits the optical signal through an industry standard LC connector. Wavelength control to 100GHz ITU grid and optical power monitoring over life is also integrated within EFFECT Photonics' Optical System-on-Chip and packaging technology.

On the receive path, DC balanced serial NRZ data is efficiently converted into the electrical domain through the Receiver Optical Sub-Assembly (ROSA) which contains an Avalanche PhotoDiode Receiver (APD) and Trans-Impedance Amplifier (TIA) with Limiting output to the host.

Optional NarroWave feature enables wavelength auto-tuning and remote diagnostics monitoring over fiber.

Applications

- Mobile Fronthaul
- CPRI 2 - 8 and eCPRI (10G)
- 10G DWDM Point-to-Point links
- Multi-point networks
- Local area networks (LAN)
- 10GBase-ER Ethernet applications
- 1G FC to 10G FC
- 10G OTN
- Storage area networks (SAN)

Standards

- SFF-8083, rev 1.7
- SFF-8418, rev 1.4
- SFF 8419, rev 1.3
- SFF-8432, rev 5.1
- SFF-8472, rev 12.2
- SFF-8690, rev 1.4
- IEEE 802.3x
- ITU-T G.709
- ITU-T G.694.1

Compliances

- Telcordia GR-468-CORE
- Telcordia GR-20-CORE
- Telcordia GR-63-CORE, NEBS
- Telcordia GR-326-CORE
- IEC 60825-1 Ed 2 Class 1
- FDA 21 CFR Ch1 Class 1
- RoHS 6/6 Lead Free

Module Wavelength Assignments and Part Numbers

Five part numbers to cover the ITU-T C-band frequency range from 192.0THz to 195.9THz with 100GHz grid spacing.

Band	Part Number	Wavelength (nm)	Frequency (THz)	Spacing (GHz)	C-Band	No. of Channels
1	EPD1011E1B	1561.42 to 1554.94	192.00 to 192.80	100	C20 - C28	9
2	EPD1011E2B	1554.94 to 1548.51	192.80 to 193.60	100	C28 - C36	9
3	EPD1011E3B	1548.51 to 1542.14	193.60 to 194.40	100	C36 - C44	9
4	EPD1011E4B	1542.14 to 1535.82	194.40 to 195.20	100	C44 - C52	9
5	EPD1011E5B	1535.82 to 1531.12	195.20 to 196.00	100	C52 - C60	9

Part Number Options

SFP+, I- temp, 40km, DWDM Narrow Tunable 9-channel, band x

x (band)	Part Number	Options ¹
1..5	EPD1011ExB-GM01	-
1..5	EPD1011ExB-GM02	Including NarroWave
1..5	EPD1011ExB-GM03	Including NarroWave, Automatic Tuning activated

¹ For other optional features, please contact your local EFFECT Photonics sales representative

Optical Characteristics

Transmit Characteristics

Parameter	Min	Max	Unit
Data rate	1.0	11.3	Gbps
Optical output power	-1	+5	dBm
Extinction ratio (NRZ, filtered)	9.0		dB

Receive Characteristics²

Parameter	Min	Max	Unit
Data rate	1.0	11.3	Gbps
Receiver wavelength range	1528.38	1567.95	nm
Receiver power range at BER 1e-12	-23	-7	dBm
Receiver optical reflectance		-27	dB
LOS assert	-35		dBm
LOS de-assert		-28	dBm
LOS assert/de-assert hysteresis	0.5		dB

² Measured with fixed RxDTV; 0.55nm 3dB filter BW; OSNR resolution 0.2 nm; PRBS 2³¹-1; with external clock and data recovery (CDR) board; NarroWave disabled

Contact information

e-mail: sales@effectphotonics.com | website: www.effectphotonics.com

© EFFECT Photonics 2022. All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights. EFFECT Photonics assumes no responsibility or liability whatsoever for any failure or unexpected operation resulting from misuse, neglect, improper installation, repair or improper handling or unusual physical or electrical stress including, but not limited to, exposure to parameters beyond the specified maximum ratings or operation outside the specified range. EFFECT Photonics' PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF EFFECT PHOTONICS PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE UNDERTAKEN SOLELY AT THE CUSTOMER'S OWN RISK. Should a customer purchase or use EFFECT Photonics products for any such unauthorized application, the customer shall indemnify and hold EFFECT Photonics and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs damages and attorney fees which could arise. Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

All product specifications are subject to change without notice. Last update September 2022. PB-00006-06